EUROREPAR

Technical Data Sheet



SELECT 15W-40

Multigrade motor oil

Specifications:

ACEA A3/B4; API SL/CF

Suitable for use in applications requiring: VW 501 01, VW 505 00; MB 229.1

Product Features:

- Multigrade motor oil designed to provide a high level of performance and protection under most conditions.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.870 g/cm^3
Viscosity @ 100°C	13.4 cSt
Viscosity @ 40°C	94 cSt
Viscosity Index	143
Viscosity CCS @ -20°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.40%
Zinc	0.12%
Calcium	0.36%
Phosphorus	0.12%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



A3/B4 10W-40

High performance motor oil

Specifications:

ACEA A3/B4; API SN/CF

Product Features:

- Semi Synthetic based engine oil.
- High performance.
- For petrol and diesel engines without particle filters.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.865 g/cm3
Viscosity @ 100°C	13.7 cSt
Viscosity @ 40°C	92 cSt
Viscosity Index	151
Viscosity CCS @ -25°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.30%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



A3/B4 5W-40

Synthetic technology engine oil

Specifications:

ACEA A3/B4; API SN/CF

Meets requirements of: VW 502 00, VW 505 00; MB 229.3; RN0700, RN0710

Product Features:

- Synthetic Technology Engine Oil.
- Very High Performance.
- For petrol and diesel engines (multi-valves, turbo, with or without catalytic converter).

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.850 g/cm3
Viscosity @ 100°C	14.5 cSt
Viscosity @ 40°C	89 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.10%
Zinc	0.12%
Calcium	0.30%
Phosphorus	0.10%
Colour	Brown
Flash Point (Closed Cup)	210°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



C3 5W-40

Synthetic technology engine oil

Specifications:

ACEA C3; API SN/CF

Meets requirements of: MB 229.31, MB 226.5;
VW 502 00, VW 505 00, VW 505 01; Porsche A40;
FORD WSS M2C917-A

Product Features:

- Synthetic Technology Engine Oil.
- High performance mid SAPS oil.
- For modern petrol and diesel engines including those fitted with exhaust after-treatment units.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.850 g/cm3
Viscosity @ 100°C	13.5 cSt
Viscosity @ 40°C	78 cSt
Viscosity Index	160
Viscosity CCS @ -30°C	6000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



A5/B5 5W-30

High performance motor oil

Specifications:

ACEA A5/B5; API SL/CF

Product Features:

- Semi Synthetic based engine oil.
- For petrol and diesel engines including those with fuel injected, multivalved and turbo charged engines.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.852 g/cm3
Viscosity @ 100°C	10.4 cSt
Viscosity @ 40°C	58 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	4600 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	1.00%
Zinc	0.11%
Calcium	0.32%
Phosphorus	0.11%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM A5/B5 5W-30

Synthetic technology engine oil

Specifications:

ACEA A5/B5; API SL/CF

Meets requirements of: Ford WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C, WSS-M2C913-D; STJLR.03.5003

Product Features:

- Synthetic Technology Engine Oil.
- Designed for new generations of petrol and diesel engines, intended for use at extended drain Intervals.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.848 g/cm^3
Viscosity @ 100°C	9.9 cSt
Viscosity @ 40°C	55 cSt
Viscosity Index	166
Viscosity CCS @ -35°C	4000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.26%
Phosphorus	0.10%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM C1 5W-30

Synthetic technology engine oil

Specifications:

ACEA C1

Meets requirements of: FORD WSS-M2C934-B; STJLR.03.5005

Product Features:

- Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.845 g/cm3
Viscosity @ 100°C	10.0 cSt
Viscosity @ 40°C	56 cSt
Viscosity Index	167
Viscosity CCS @ -30°C	4000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.07%
Phosphorus	0.05%
Colour	Brown
Flash Point	230°C
Pour Point	-42°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM C3 5W-30

Synthetic technology engine oil

Specifications:

ACEA C3; API SN/CF

Meets requirements of: BMW LL-04; MB 229.31, 229.51, 229.52; VW 502 00, VW 505 01; dexos2

Product Features:

- Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.850 g/cm3
Viscosity @ 100°C	12.2 cSt
Viscosity @ 40°C	70 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	6000 cP
T.B.N.	7.8 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.18%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM 504/507 5W-30

Synthetic technology engine oil

Specifications:

ACEA C3

Meets requirements of: VW 504 00, VW 507 00; BMW LL-04; PORSCHE C30; MB 229.51

Product Features:

- Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.845 g/cm3
Viscosity @ 100°C	11.7 cSt
Viscosity @ 40°C	65 cSt
Viscosity Index	177
Viscosity CCS @ -30°C	5700 cP
T.B.N.	8.6 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM C4 5W-30

Synthetic technology engine oil

Specifications:

ACEA C4

Meets requirements of: RN0720; MB 226.51

Product Features:

- Very high performance Synthetic Technology Engine Oil.
- Specially designed for the latest Renault engines with particulate filters.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.847 g/cm3
Viscosity @ 100°C	12.2 cSt
Viscosity @ 40°C	73 cSt
Viscosity Index	165
Viscosity CCS @ -30°C	5900 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.49%
Zinc	0.07%
Phosphorus	0.05%
Colour	Brown
Flash Point	230°C
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PREMIUM C5 5W-20

Synthetic technology engine oil

Specifications:

ACEA C5; API SN

Meets requirements of: FORD WSS M2C948-B; STJLR.03.5004

Product Features:

- Synthetic Technology Engine Oil.
- For new generations of petrol and diesel engines, designed for vehicles fitted with post-treatment systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.847 g/cm3
Viscosity @ 100°C	8.0 cSt
Viscosity @ 40°C	43 cSt
Viscosity Index	161
Viscosity CCS @ -30°C	4300 cP
T.B.N.	8.1 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.09%
Calcium	0.18%
Phosphorus	0.09%
Colour	Brown
Flash Point	230°C
Pour Point	-36°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



PROTECT GF 0W-20

Synthetic technology engine oil

Specifications:

API SN; ILSAC GF-5

Product Features:

- Synthetic Technology Engine Oil.
- High Performance.
- For modern petrol vehicles and most petrol-electric hybrids.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.844 g/cm3
Viscosity @ 100°C	8.5 cSt
Viscosity @ 40°C	44 cSt
Viscosity Index	174
Viscosity CCS @ -35°C	5000 cP
T.B.N.	8.0 mg KOH/g
Sulphated Ash Mass	0.80%
Zinc	0.10%
Calcium	0.13%
Phosphorus	0.08%
Colour	Brown
Flash Point	230°C
Pour Point	-45°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



MTF FS 75W-90

Oil for manual gearboxes

Specifications:

Suitable for use in applications requiring:

Ford WSD-M2C200-C, Ford WSD-M2C200-B; GM 1940768, GM 1940182, GM 1940764; Volvo 97309; Volkswagen G 50; API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90); Special transmission oil; Castrol BOT 130

Product Features:

- Synthetic Manual Transmission Fluid.
- Excellent bearing and gear protection, proven synchroniser performance.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.845 g/cm^3
Viscosity @ 100°C	16.0 cSt
Viscosity @ 40°C	100 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



MTF SS 75W-90

Oil for manual gearboxes

Specifications:

Suitable for use in applications requiring: API GL-5, API GL-4; MIL 2105D

Product Features:

- Semi Synthetic Gear Oil.
- For modern five and six speed gear boxes and differentials.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.853 g/cm^3
Viscosity @ 100°C	15.0 cSt
Viscosity @ 40°C	95 cSt
Phosphorus	0.04%
Colour	Light Straw
Pour Point	-36°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



MTF M4 80W-90

Oil for manual gearboxes

Specifications:

Suitable for use in applications requiring: API GL-4, API GL-3; Ford SQ-M2C9008-A; MB 235.1; MIL 2105

Product Features:

- Mineral Gear Oil.
- Extreme pressure gear oil for manual gearboxes.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.875 g/cm^3
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	132 cSt
Phosphorus	0.01%
Colour	Brown
Pour Point	-30°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



MTF M5 80W-90

Oil for manual gearboxes

Specifications:

Suitable for use in applications requiring: API GL-5; Ford M2C197-A, MB 235.0; MIL 2105D

Product Features:

- Mineral Gear Oil.
- Extreme pressure gear oil for manual gearboxes and differentials.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.875 g/cm^3
Viscosity @ 100°C	14.0 cSt
Viscosity @ 40°C	129 cSt
Phosphorus	0.03%
Colour	Brown
Pour Point	-30°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



ATF MDX 2

Oil for automatic transmission

Specifications:

Suitable for use in applications requiring: ATF;
Type A Suffix A; Dexron® B, Dexron®II, Dexron®IID;
MB 236.2, MB 236.6

Product Features:

- Mineral Automatic Transmission Fluid.
- For many automatic transmissions, torque converters and power steering systems.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.855 g/cm^3
Viscosity @ 100°C	6.9 cSt
Viscosity @ 40°C	34 cSt
Phosphorus	0.01%
Colour	Red
Pour Point	-45°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



ATF SSDX 3

Oil for automatic transmission

Specifications:

Suitable for use in applications requiring: Dexron® II, Dexron® IID, Dexron® IIE, Dexron® III

Product Features:

- Semi Synthetic Automatic Transmission Fluid.
- Protects against foaming, corrosion, oxidation and wear.
- Provides quiet and smooth gear shift.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.853 g/cm^3
Viscosity @ 100°C	7.0 cSt
Viscosity @ 40°C	34 cSt
Phosphorus	0.01%
Colour	Red
Pour Point	-45°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



ATF FSDX 6

Oil for automatic transmission

Typical Inspection Data:	
Density @ 20°C	0.840 g/cm^3
Viscosity @ 100°C	6.4 cSt
Viscosity @ 40°C	33 cSt
Phosphorus	0.02%
Colour	Red
Pour Point	-45°C

Specifications:

Suitable for use in applications requiring: Nissan Matic J, Nissan Matic D; Special ATF Honda ATF-Z1; Volvo 1161540; VW G 052 162, VW G 055 540; ZF-11A, ZF-11B; GM 1940771; Allison C-4; JWS 3309, JWS 3324 (ATF WS); LT71141; Mercon; ATF, Mercon LV; ATF, Mercon SP; ATF, Mercon V; SP-II; ATF, SP-III; ATF; Toyota Type T-II,Toyota Type T-IV; Chrysler MS 7176E (ATF +3), Chrysler MS 9602 (ATF +4); Dexron® II, Dexron® II D, Dexron® IIE, Dexron® IIE + Mercon, Dexron® III, Dexron® III (G), Dexron® (H), Dexron® III + Alison C-4, Dexron® III + Mercon, Dexron® VI; Ford ESP-M2C166-H, Ford M2C138-CJ, Ford WSS-M2C202-B, MB 236.10, MB 236.6, MB 236.7, MB 236.9

Product Features:

- Synthetic Automatic Transmission & Power Steering Fluid.
- Offers excellent frictional stability, anti-shudder & anti-wear properties.
- For automatic transmissions and power steering systems for many European, American and Asian vehicles.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com

EUROREPAR

Technical Data Sheet



ATF FSDCT

Oil for semi automatic transmissions

Specifications:

Suitable for use in applications requiring: VW G 052 182 A2 or A6 (fluid); BMW Drivelogic 7-speed (Getrag) DCTF-1

Product Features:

- Dual Clutch Transmission Fluid.
- High Performance. For use in the widest range of vehicle makes fitted with DSG or DCT wet transmissions.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Typical Inspection Data:	
Density @ 20°C	0.840 g/cm^3
Viscosity @ 100°C	7.3 cSt
Viscosity @ 40°C	36 cSt
Phosphorus	0.02%
Colour	Brown
Pour Point	-36°C

Updated: 04/09/2020 (13:57)

PSA Automobiles SA, 2-10 Boulevard de l'Europe, 78300, Poissy, France.
Tel: +33 1 61 45 45 45 www.eurorepar.com