Products for tyres

December 2018



PRODUCT ADVANTAGES

- → ***Quality:*** *mounting parts are of premium quality while repair products are identical to those provided by tyre specialists.*
- → ***Robustness:*** *the quality of the consumables ensures long-term tyre balancing and repair performance.*

In connection with its Eurorepar Reliance tyre range, Eurorepar is expanding its **range of products and consumables** for tyre repair.

The range consists of consumables for **tyre mounting** – balancing weights, valves, caps, paste and mounting lubricants – and consumables for **tyre repair** – plugs, patches and vulcanizing products – as well as the **associated tools** – valve core remover, valve remover.

It allows professional mechanics to provide a comprehensive service rivalling that offered by the best tyre specialists.

Reference list

Our parts are guaranteed for 2 years*

RENOVATION

- **All wear parts are replaced** by original or premium-quality components satisfying the original specifications;
- **All re-usable components are subject to specific cleaning and treatment** to ensure correct mechanical and electrical performance;

TECHNICAL CHARACTERISTICS

Range of 28 references adapted to the Eurorepar Reliance range and any other tyre brand.

Tyre mounting:

- All-purpose zinc weights ranging from 5 g to 45 g to be clipped onto steel and aluminium rims.
- 1 box of 60 g adhesive tapes and 1000 x 5 g roll.
- 3 types of valve to cover all passenger car models with a universal cap.
- 1 valve core remover, 1 tyre bead/rim sealing product, 2 mounting products (paste and spray).

Tyre repair:

- 2 sets of self-vulcanizing patches, 45x45 and D65.
- Repair plugs: 3 mm and 6 mm diameters, in boxes containing 18 pieces.
- 1 vulcanizing solution and 1 liquid buffer.

CONDITIONS FOR REPLACEMENT

To be able to use these products correctly, certain conditions are necessary:

- **The puncture must be exclusively be on the tread**. Any repair of a puncture, impact or laceration on the flanks involves, wherever possible, a hot vulcanization process carried out by a specialised professional.
- The vehicle must not have been subjected to prolonged immobilisation with the flat tyre (destruction of the tyre structure).
- It should be ensured that the internal structure is not damaged by driving on a flat tyre.

Our parts are guaranteed 2 years* against any manufacturing or material defect.**
(*) For Citroen, DS, Peugeot, Euro Repar Car Service repair networks: the warranty runs for 2 years, parts AND labour included.
(**) For the conditions of application, contact your dealer.

SECURE LABELS
Avoids any risk to fake parts and guarantees their quality.

www.eurorepar.com